

Trimble RTS771 Robotic Total Station

High Precision Positioning

For your most demanding projects, this 1" instrument raises the bar in high-accuracy positioning for general contractors.

- Video-Assisted Control**
 Trimble VISION™ gives you the power to see everything the instrument sees without a trip back to the tripod. Direct your layout with live video images on the Trimble Field Tablet. Now you are free to capture measurements, to prism or reflectorless surfaces, with point and click efficiency.
- Visual Verification**
 To provide an accurate documentation of the design and field image that is displayed within the Trimble Field Link software, job data including points and linework are overlaid on the camera image.

ADVANCED TOTAL STATION TECHNOLOGY

Trimble MagDrive™ Servo Technology provides for exceptional speed and accuracy with smooth, silent operation.

Trimble SurePoint™ Technology ensures accurate measurements by automatically correcting for unwanted movement due to wind, sinkage, and other factors.

Trimble MultiTrack™ technology locks on and tracks passive prisms for control measurements and active targets for dynamic measurement, stakeout and grade control.

BUILT FOR CONSTRUCTION

For construction applications, you need a measurement solution with optimal speed, accuracy and reliability. Combine the Trimble DR HP Precision EDM with Trimble VISION and you have the flexibility to tackle the most demanding projects.

- 1" angle accuracy for high-precision positioning applications.
- Automatic Servo Focus sets the optical focus for quick manual aiming when laying out points in DR mode.
- Combine with Trimble Field Link software running on the Trimble Field Tablet to optimize your accuracy and productivity.

Key Features:

- Trimble VISION**
 video-assisted robotic measurement
- Visual verification** with data overlay and photo documentation
- MagDrive technology for maximum speed and efficiency
- MultiTrack technology offers the choice between passive and active tracking



EDM	Servo Control	Angle Accuracy	Hardware Options
DR HP	Robotic, Autolock	1"	Trimble VISION

GENERAL SPECIFICATIONS

PERFORMANCE

Angle measurement accuracy (standard deviation based on DIN 18723) 1" (0.3 mgon)
 Angle display (least count) 0.1" (0.01 mgon)
 Distance measurement

Typical Accuracy	50 m (164 ft)	100 m (328 ft)	200 m (656 ft)	300 m (984 ft)
Prism mode				
Standard	2 mm (5/64")	2 mm (5/64")	3 mm (1/8")	4 mm (5/32")
Tracking	5 mm (13/64")	5 mm (13/64")	6 mm (15/64")	6 mm (15/64")
DR mode				
Standard	3 mm (1/8")	3 mm (1/8")	4 mm (5/32")	5 mm (13/64")
Tracking	10 mm (25/64")	10 mm (25/64")	11 mm (7/16")	11 mm (7/16")

Measuring time
 Prism mode
 Standard 2.5 s
 Tracking 0.4 s
 Averaged observations 2.5 s per measurement
 DR mode
 Standard 3–15 s
 Tracking 0.4 s

Range (under standard clear conditions^{1,2})
 Prism mode
 1 prism 3,000 m (9,800 ft)
 Shortest range 1.5 m (4.9 ft)

	Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
White card (90% reflective)³	>150 m (492 ft)	150 m (492 ft)	70 m (229 ft)
Gray card (18% reflective)³	>120 m (394 ft)	120 m (394 ft)	50 m (164 ft)
Shortest range	1.5 m (4.9 ft)		

EDM SPECIFICATIONS

Light source Laserdiod 660 nm; Laser class 1 in Prism mode
 Laser class 2 in DR mode
 Laser pointer coaxial (standard) Laser class 2
 Beam divergence Prism mode
 Horizontal 4 cm/100 m (0.13 ft/328 ft)
 Vertical 4 cm/100 m (0.13 ft/328 ft)
 Beam divergence DR mode
 Horizontal 2 cm/50 m (0.066 ft/164 ft)
 Vertical 2 cm/50 m (0.066 ft/164 ft)
 Atmospheric correction -130 ppm to 160 ppm continuously

CAMERA

Chip Color Digital Image Sensor
 Resolution 2048 x 1536 pixels
 Focal length 23 mm
 Depth of field 3 m to infinity
 Field of view 15.5 deg x 12.3 deg
 Digital zoom 4-step (1x, 2x, 4x, 8x)
 Video streaming 5 frames/sec

1 Standard clear: No haze. Overcast or moderate sunlight with very light heat shimmer.
 2 Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.
 3 Kodak Gray Card, Catalog number E1527795.
 4 The capacity in -20 °C (-5 °F) is 75% of the capacity at +20 °C (68 °F).
 5 Bluetooth type approvals are country specific. Contact your local Trimble Authorized Distribution Partner for more information.
 6 Dependent on selected size of search window.

GENERAL SPECIFICATIONS

Leveling
 Circular level in tribrach 8/2 mm (8/0.007 ft)
 Automatic level compensator
 Type Centered dual-axis
 Accuracy 0.5" (0.15 mgon)
 Range ±5.4' (±100 mgon)
 Servo system MagDrive servo technology; integrated servo/angle sensor; electromagnetic direct drive
 Rotation speed 115 degrees/s (128 gon/s)
 Rotation time Face 1 to Face 2 2.6 s
 Positioning speed 180 degrees (200 gon) 2.6 s
 Clamps and slow motions Servo-driven, endless fine adjustment
 Centering
 Centering system Trimble 3-pin
 Optical plummet Built-in optical plummet
 Magnification/shortest focusing distance 2.3x/0.5 m to infinity (1.6 ft to infinity)
 Telescope
 Magnification 30x
 Aperture 40 mm (1.57 in)
 Field of view at 100 m (328 ft) 2.6 m at 100 m (8.5 ft at 328 ft)
 Shortest focusing distance 1.5 m (4.92 ft) to infinity
 Illuminated crosshair Variable (10 steps)
 Autofocus Standard
 Operating temperature -20° C to +50° C (-4° F to +122° F)
 Dust and water proofing IP55
 Humidity 100% condensing
 Power supply
 Internal battery Rechargeable Li-Ion battery 11.1 V, 5.0 Ah
 Operating time⁴
 One internal battery Approx. 6.5 hours
 Three internal batteries in multi-battery adapter Approx. 18 hours
 Robotic holder with one internal battery 13.5 hours
 Operating time with video robotic⁴
 One battery 5.5 hours
 Three batteries in multi-battery adapter 17 hours
 Weight
 Instrument (Servo/Autolock®) 5.15 kg (11.35 lb)
 Instrument (Robotic) 5.25 kg (11.57 lb)
 Trimble CU controller 0.4 kg (0.88 lb)
 Tribrach 0.7 kg (1.54 lb)
 Internal battery 0.35 kg (0.77 lb)
 Trunnion axis height 196 mm (7.71 in)
 Communication USB, Serial, Bluetooth⁵
 Security Dual-layer password protection

ROBOTIC RANGE

Autolock and Robotic range²
 Passive prisms 500–700 m (1,640–2,297 ft)
 Trimble MultiTrack Target 800 m (2,625 ft)
 Autolock pointing precision at 200 m (656 ft) (standard deviation)²
 Passive prisms <2 mm (0.007 ft)
 Trimble MultiTrack™ Target <2 mm (0.007 ft)
 Shortest search distance 0.2 m (.65 ft)
 Search time (typical)⁶ ~2–10 s

Specifications subject to change without notice.

© 2015, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and Autolock are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. 4D Control, Access, MagDrive, MultiTrack, SurePoint, and VISION are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022519-140 (07/15)

Building Point Ohio Valley
 1120 Ohioview Avenue | Ambridge, PA 15003
 724-266-1600 | info@bpohiovalley.com

TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

NORTH AMERICA
 Trimble Navigation Limited
 10368 Westmoor Drive
 Westminster, CO 80021
 1.916.294.2000

EUROPE
 Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim
 Germany



<http://buildings.trimble.com>